



FLAG PAVING:
PAVING RELIANT TO ENTRANCE
DOORS WITH THRESHOLD
SLOT DRAINAGE INSTALLED

BENCH:
FURNITURES STAINLESS
STEEL ALPINE BENCH ALB6

PERMEABLE PAVING:
65mm BLOCKLEY PERMEABLE
PAVOUR ON 50mm 2/6mm
CRUSHED STONE BEDDING ON
350mm 4/20mm COARSE
AGGREGATE ROAD BASE ON
GEOTEXTILE MEMBRANE ON
EXISTING SUBGRADE

TREE PROTECTION:
FURNITURES ELTHAM RANGE
TREE GRID ES 1575 MEDIUM
DUTY AND FRAME ESF 1524
WITH ASHFORD STAINLESS
STEEL TREE GUARDS ASH
750

GRASS REINFORCEMENT:
PROPRIETARY ROOT FILL
60-40 IN BODPAVE 85 500 X
500mm PLASTIC GRID GRASS
REINFORCEMENT ON 50mm
CONSOLIDATED ROOTZONE
60-40 ON GEOTEXTILE LAYER
BGT100 ON 150mm (DoT
TYPE 3, or 1X or 420)
CRUSHED ANGULAR MATERIAL
5/45mm (NO FINES)
SUB-BASE ON TENSAR
TX160 GEOGRID

PERMEABLE PAVING:
65mm BLOCKLEY PERMEABLE
PAVOUR ON 50mm 2/6mm
CRUSHED STONE BEDDING ON
350mm 4/20mm COARSE
AGGREGATE ROAD BASE ON
GEOTEXTILE MEMBRANE ON
EXISTING SUBGRADE

PAVEMENT CROSSOVER:
BY OTHERS (LA
CONTRACTOR)

